

G-BUS COMPRESSOR

Studio9 Plugins 2026

Version 1.1.1

G-Bus Compressor is an emulation of the legendary SSL 4000 G-Bus stereo bus compressor — the defining sound of countless hit records since the 1980s. Like the original hardware, it uses a feedback topology where the detector reads the VCA output rather than the input, producing the natural self-regulating "glue" that the SSL console is famous for. It features true stereo-linked RMS detection, discrete attack and release time selections, sidechain high-pass filtering, and a soft-knee gain computer that closely mirrors the behaviour of the original circuit.

The Drive control adds subtle output transformer saturation modelled on the SSL 4000 series output stage — a gentle second-harmonic warmth that adds density and presence without heavy colouration. The plugin runs with 2x oversampling and a linear-phase filter around the saturation stage, keeping aliasing artefacts inaudible and preserving phase coherence for master bus use.



Fig. 1

CONTROLS

Threshold: Sets the level (dBFS) at which compression begins. Lower values engage the compressor earlier and produce more gain reduction.

Ratio: Selects the compression ratio: 2:1 for gentle glue, 4:1 for the classic SSL sound, or 10:1 for heavy limiting.

Attack: Selects the attack time from 0.1ms to 30ms, or AUTO for program-dependent attack that follows the musical material.

Release: Selects the release time from 0.1s to 1.2s, or AUTO for the dual time-constant program-dependent release that gives the SSL its glue.

Makeup: Applies output gain (0 to +20 dB) to compensate for gain reduction.

SC HPF: Engages a 160 Hz sidechain high-pass filter to prevent low-end content from triggering excessive gain reduction on every beat.

Stereo Link: Links the left and right sidechain detectors so both channels compress together, driven by the louder side.

Drive: Adds transformer saturation from subtle warmth to noticeable colour. Best kept low (under 30%) on the master bus.

Meter Mode: Switches the VU meter between Input level, Gain Reduction, and Output level display.

PRESETS

Drums Bus

Threshold -15 dB | Ratio 4:1 | Attack 3ms | Release 0.1s
Makeup +4 dB | SC HPF ON | Stereo Link ON | Drive 20%

Guitar Bus

Threshold -12 dB | Ratio 2:1 | Attack 10ms | Release 0.3s
Makeup +3 dB | SC HPF OFF | Stereo Link ON | Drive 35%

Mix Bus

Threshold -10 dB | Ratio 4:1 | Attack 30ms | Release AUTO
Makeup +2 dB | SC HPF ON | Stereo Link ON | Drive 10%

STUDIO9 PLUGINS FREEWARE LICENSE

Copyright (c) 2026 Studio9 Plugins

This software is provided free of charge for both personal and commercial use.

You may:

- * Install and use this software free of charge.
- * Use this software in personal, educational, non-profit, and commercial environments.

You may not:

- * Sell, resell, rent, lease, or sublicense this software.
- * Modify, reverse engineer, decompile, or create derivative works from this software.
- * Redistribute this software without prior written permission from Studio9 Plugins.
- * Bundle this software with any hardware product, software product, or commercial offering without prior written permission from Studio9 Plugins.

Any authorized redistribution must include this license and all copyright notices.

DISCLAIMER

THIS SOFTWARE IS PROVIDED "AS IS" WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED.

STUDIO9 PLUGINS SHALL NOT BE LIABLE FOR ANY LOSS, DAMAGE, CLAIM, OR LIABILITY OF ANY KIND ARISING FROM THE USE OF OR INABILITY TO USE THIS SOFTWARE.

USE OF THIS SOFTWARE IS ENTIRELY AT YOUR OWN RISK.

By installing or using this software, you agree to the terms of this license.